

# KLONDIKE CVT Fluid Full Synthetic



## PRODUCT DESCRIPTION

KLONDIKE Full Synthetic CVT Fluid is a premium performance, fully synthetic formulation designed for modern Continuously Variable Transmission designs in passenger cars. This specially formulated combination of 100% synthetic base oils and state-of-the-art additive technology ensures peak performance and outstanding fuel economy across a broad range of applications using belt or chain driven technology.

## APPLICATIONS

KLONDIKE Full Synthetic CVT Fluid is highly advanced and designed for use in Continuously Variable Transmissions manufactured by North American, European, Asian, and other manufacturers around the world. This is a truly universal CVT fluid ideal for a broad application range.

Typical applications include:

- Modern passenger cars utilizing advanced CVT technology.



## FEATURES AND BENEFITS

KLONDIKE Full Synthetic CVT Fluid is formulated with premium full synthetic base oils and technologically advanced additives. This high performance chemistry is specifically engineered for and unique to CVT applications; offering outstanding anti-shudder durability, friction stability, anti-wear protection, oxidation stability, and advanced low and high temperature operation characteristics. Anti-oxidation additives minimize the formation of deposits, sludge, varnish, and foam; and demonstrate outstanding fluid life and component durability. Advanced friction modifiers combined with optimized base oil viscosity enhance and maintain fuel economy benefits as designed by the OEM.

KLONDIKE Full Synthetic CVT Fluid provides the necessary wear protection, viscometrics, and frictional properties required to fulfill the demands of many North American, European, and Asian manufactured Continuously Variable Transmissions. This multi-functional formulation has been extensively field tested to demonstrate its compatibility in a wide variety of applications.

KLONDIKE Full Synthetic CVT Fluid delivers value through the following benefits:

- **Full synthetic** – premium synthetic base oils and advanced additive technology maintains fuel economy and operating efficiency.
- **Anti-wear protection** – minimizes premature wear and maintains its properties at high temperatures under extreme loads or in severe operating conditions.
- **All climate application** – highly stable even at extreme high and low temperatures for year-round protection and performance.
- **Extended service life** – retains frictional performance properties and protects against oxidation, rust, and corrosion.
- **Compatibility** – ideal for top-up or complete replacement for OEM fluids.



# KLONDIKE CVT Fluid Full Synthetic

## SPECIFICATIONS AND APPROVALS

KLONDIKE Full Synthetic CVT Fluid is designed for use in most modern CVT applications including (but not limited to):

- Audi/VW (TL 52180; G 052 180; G 052 516)
- BMW 8322 0 136 376/8322 0 429 154 (EZL799/799A)
- Daihatsu Amix CVTF-DC, CVTF-DFE
- Dodge / Jeep (NS-2 / CVTF+4/Mopar CVT 4)
- Ford CFT30/WSS-M2C933-A /Motorcraft XT-7-QCFT
- GM/Saturn (DEX-CVT, CVTF I-Green2)
- Honda (HMMF, HCF-2)
- Hyundai/Kia CVTF (SP-CVT-J1)
- Mazda CVTF 3320
- Mercedes Benz CVT28, 236.20
- Mini Cooper (EZL 799/ EZL 799A/ZF CVT V1)
- Mitsubishi DiaQueen (CVTF-J1, CVTF-J4)
- Nissan (NS-1, NS-2, NS-3)
- Punch EZL 799/EZL 799A
- Renault ELFMATIC
- Shell Green 1V
- Subaru (NS-2 / Lineartronic CVTF, i-CVTF, K0425Y0710) e-CVTF, High Torque
- Suzuki (TC / NS-2 / CVTF Green 1, Green 2, CVTF 3320)
- Toyota (CVTF TC, CVTF FE)

All specifications listed are current to the best of our knowledge. Some specifications listed may supersede previous or obsolete numbers.

Other applicable uses may exist. Please contact KLONDIKE for more information.

## HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit [www.klondikelubricants.com](http://www.klondikelubricants.com) or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

## TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	FULL SYNTHETIC CVT FLUID
Specific @ 15.6°C	ASTM D4052	0.8538
API Gravity	ASTM D287	34.2
Viscosity @ 40°C, cSt	ASTM D445	33.8
Viscosity @ 100°C, cSt	ASTM D445	7.21
Viscosity Index	ASTM D2270	185
Brookfield @ -40°C, cP	ASTM D2983	12,300
Pour Point, °C	ASTM D5950	-51
Flash Point, COC, °C	ASTM D92	200
Color	ASTM D1500	Amber

All stated physical properties are typical of standard production and may vary.

## BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

**KLONDIKE Lubricants Corporation**

Toll-free 1-877-293-4691

[info@klondikelubricants.com](mailto:info@klondikelubricants.com)  
[www.klondikelubricants.com](http://www.klondikelubricants.com)

