SAFETY DATA SHEET



1. Identification

Product identifier KLONDIKE Long Life Turbine Oil ISO 32

Other means of identification

Product code ISO 32 Long Life Turbine Oil

Recommended use Turbine Oil None known. Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name KLONDIKE Lubricants Corporation

Address 3078 275th Street

Langley, BC V4W 3L4

Canada

General Information 1-877-293-4691 **Telephone**

Website www.klondikelubricants.com E-mail info@klondikelubricants.com

Chemtrec (Within US) **Emergency phone number** 1-800-424-9300

Chemtrec (International) 1-703-527-3887

Supplier Refer to Manufacturer

2. Hazard(s) identification

Physical hazards This mixture does not meet the classification criteria according to OSHA HazCom 2012. **Health hazards** This mixture does not meet the classification criteria according to OSHA HazCom 2012. **Environmental hazards** This mixture does not meet the classification criteria according to OSHA HazCom 2012. **OSHA** defined hazards This mixture does not meet the classification criteria according to OSHA HazCom 2012.

Label elements

None. Hazard symbol Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

No OSHA defined hazard classes. classified (HNOC)

Other hazards which do not result in classification: May cause mild skin and eye irritation. May cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can

be fatal.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates, (petroleum),	HEAVY BASE OILS (HEAVY PARAFFINIC	64742-54-7	60 - 100
Hydrotreated Heavy Paraffinic	HYDROTREATED DISTILLATE)		

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Material name: KLONDIKE Long Life Turbine Oil ISO 32 2166 Version #: 02 Issue date: 01-19-2017

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Never give anything by mouth to a victim

who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

May be mildly irritating to skin, eyes and respiratory system. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms may include stinging and tearing. Symptoms may include upper respiratory irritation, coughing, and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Specific methods

General fire hazards
Hazardous combustion

products

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Ventilate the contaminated area. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

Carbon oxides. Sulphur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Hydrocarbons.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Use only non-sparking tools. Avoid inhalation of vapors and spray mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not ingest. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Handle and open container with care.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits
No exposure limits noted for ingredient(s).

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes

that may be generated during handling or thermal processing.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Provide an emergency eye wash fountain and

quick drench shower in the immediate work area.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Advice should be sought from glove suppliers.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Seek advice from

respiratory protection specialists.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorDark amber.

Odor Mild petroleum odor.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling > 280 °C (536 °F)

range

Flash point 212.0 °C (413.6 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 46 cSt

Other information

Specific gravity 0.86

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not use in

areas without adequate ventilation.

Strong oxidizing agents.

Incompatible materials

Hazardous decomposition

products

Carbon oxides. Phosphorus oxides. Sulfur oxides. Nitrogen oxides (NOx). Hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Inhalation Inhalation of vapors/fumes generated by heating this product may cause respiratory irritation with

throat discomfort, coughing or difficulty breathing.

Skin contact May cause mild skin irritation.

Eve contact May cause mild eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

May cause mild skin and eye irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms may include stinging and tearing. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing, and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Information on toxicological effects

Acute toxicity See below for individual ingredient acute toxicity data.

Components Species Test Results

Distillates, (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat > 5 mg/l, 4 Hours (Mist)

Oral

LD50 Rat > 15000 mg/kg

Skin corrosion/irritation May be irritating to the skin.

Serious eye damage/eye

irritation

Direct contact may cause very mild, temporary irritation and redness.

Respiratory or skin sensitization

Respiratory sensitization This product is not expected to cause respiratory sensitization.

Skin sensitization Not expected to be a skin sensitizer.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified as a specific target organ toxicity -single exposure.

Specific target organ toxicity -

specific larger org

Not classified as a specific target organ toxicity -repeated exposure.

repeated exposure

Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

^{*} Estimates for product may be based on additional component data not shown.

Further information This product has no known adverse effect on human health.

Not expected to be hazardous by OSHA criteria. Aspiration toxicity

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Species Test Results Components

Distillates, (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)

Aquatic

Acute

EC50 Crustacea Water flea (Daphnia magna) > 10000 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Chronic

NOEC Crustacea Water flea (Daphnia magna) 10 mg/l, 21 days

Distillates, (petroleum), Hydrotreated Heavy Paraffinic is considered to be not readily Persistence and degradability

biodegradable.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

Material name: KLONDIKE Long Life Turbine Oil ISO 32 2166 Version #: 02 Issue date: 01-19-2017

^{*} Estimates for product may be based on additional component data not shown.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 01-19-2017

Version # 02

2166 Version #: 02 Issue date: 01-19-2017

Material name: KLONDIKE Long Life Turbine Oil ISO 32

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information in this document was written based on the best knowledge and experience currently available, and is offered for your consideration and guidance when exposed to this product. KLONDIKE Lubricants Corporation disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this document does not apply to use with any other product or in any other process. This document may not be changed, or altered in any way without the expressed knowledge and permission of KLONDIKE Lubricants Corporation. The information in the sheet was written based on the best knowledge and experience currently available.