SAFETY DATA SHEET



1. Identification

Product identifier KLONDIKE SAE 10W-30 CK-4 Heavy Duty Synthetic Blend Engine Oil

Other means of identification

Product code 10W-30 CK-4 Synthetic Blend

Recommended use Heavy Duty Engine Oil

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name KLONDIKE Lubricants Corporation

Address 3078 275th Street

Langley, BC V4W 3L4

Canada

Telephone General Information 1-877-293-4691

Website www.klondikelubricants.com
E-mail info@klondikelubricants.com

Emergency phone number Chemtrec (Within US) 1-800-424-9300

Chemtrec (International) 1-703-527-3887

Supplier Refer to Manufacturer

2. Hazard(s) identification

Physical hazards
This mixture does not meet the classification criteria according to OSHA HazCom 2012.
This mixture does not meet the classification criteria according to OSHA HazCom 2012.
This mixture does not meet the classification criteria according to OSHA HazCom 2012.
This mixture does not meet the classification criteria according to OSHA HazCom 2012.
This mixture does not meet the classification criteria according to OSHA HazCom 2012.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

May cause mild skin and eye irritation. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Base Oil	HYDROTREATED HEAVY NAPHTHENIC DISTILLATE (PETROLEUM)	64742-52-5	60 - 100
Highly Refined Light Mineral Base Oil	Not Available	64742-55-8	7 - 13
Zinc, Dithiophosphate Di-c1-14-alkyl Esters	PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS.	68649-42-3	0.1 - 1.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret as allowed by 29CFR1910.1200.

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Call a physician if symptoms develop or

persist.

Skin contact Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if

irritation develops and persists.

Ingestion Do not induce vomiting. Rinse mouth. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Get medical attention if symptoms occur.

Most important

General information

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Evacuate area and fight fire from a safe distance. Ventilate the contaminated area. Remove all sources of ignition. Move containers from fire area if you can do so without risk. Cool containers / tanks with water spray. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Specific methods

General fire hazards

Hazardous combustion products

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Phosphorus oxides. Sulphur oxides.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Twoid prolonged exposure. Observe good industrial mygleric practices.

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S OSHA	
----------	--

Components	Туре	Value	Form	
Zinc, Dithiophosphate	TWA		None	
Di-c1-14-alkyl Esters (CAS 68649-42-3)				

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Highly Refined Light Mineral Base Oil (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
Petroleum Base Oil (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form	
Highly Refined Light Mineral Base Oil (CAS 64742-55-8)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Petroleum Base Oil (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
·	TWA	5 mg/m3	Mist.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

500 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves. Advice should be sought from glove suppliers.

Other Wear appropriate chemical resistant clothing.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. Seek advice from respiratory protection specialists.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorAmber.

Odor Mild petroleum odor.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point and boiling280 °C (536 °F)

range

Flash point 215.0 °C (419 °F)
Evaporation rate Not available.
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

10 %

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

< 0.01 kPa Vapor pressure

Vapor density 10

Not available. Relative density

Solubility(ies)

Insoluble Solubility (water) Partition coefficient Not available. (n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Specific gravity 0.86

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not use in

areas without adequate ventilation.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

None known, refer to hazardous combustion products in Section 5.

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause discomfort if swallowed.

Inhalation May cause irritation to the respiratory system.

Skin contact May cause mild skin irritation. Eye contact May cause mild eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause mild skin and eye irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing, and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Information on toxicological effects

May cause mild irritation to skin, eyes and respiratory system. May cause irritation of the **Acute toxicity**

gastrointestinal tract.

Test Results Components **Species**

Highly Refined Light Mineral Base Oil (CAS 64742-55-8)

Acute Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat > 4000 mg/m3, 4 hours

Oral

LD50 Rat > 2000 mg/kg Components Species Test Results

Petroleum Base Oil (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 5.23 mg/l, 4 hours Mist

Oral

LD50 Rat > 5000 mg/kg

Zinc, Dithiophosphate Di-c1-14-alkyl Esters (CAS 68649-42-3)

Acute

Dermal

LC50 Rabbit No data in literature

Inhalation

LC50 Rat No data in literature

Oral

LD50 Rat 26100 mg/kg

Skin corrosion/irritation May be irritating to the skin.

Serious eye damage/eye May be irritating to eyes.

irritation

Respiratory or skin sensitization

Respiratory sensitization This product is not expected to cause respiratory sensitization.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Highly Refined Light Mineral Base Oil (CAS 64742-55-8) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified as a specific target organ toxicity -single exposure.

Specific target organ toxicity -

repeated exposure

Not classified as a specific target organ toxicity -repeated exposure.

Chronic effects Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Further information This product has no known adverse effect on human health.

Aspiration toxicity Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

KLONDIKE SAE 10W-30 CK-4 Heavy Duty Synthetic Blend Engine Oil (CAS Mixture)

Aquatic

Acute

Crustacea EC50 Daphnia 9.999 mg/l, 48 hours estimated Fish LC50 Fish 9.901 mg/l, 96 hours estimated

Components Species Test Results

Highly Refined Light Mineral Base Oil (CAS 64742-55-8)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours

^{*} Estimates for product may be based on additional component data not shown.

Components		Species	Test Results	
Fish	LC50	Fathead minnow (Pimephales prom	elas) > 100 mg/l, 96 hours	
Chronic				
Crustacea	NOEC	Water flea (Daphnia magna)	10 mg/l, 21 days	
Zinc, Dithiophosphate	Di-c1-14-alkyl Este	ers (CAS 68649-42-3)		
Aquatic				
Acute				
Algae	EC50	Green algae (Selenastrum capricornutum)	1 - 5 mg/l, 96 hours	
Crustacea	EC50	Water flea (Daphnia magna)	1 - 1.5 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales prom	elas) 1 - 5 mg/l, 96 hours	
Chronic				
Algae	NOEC	Green algae (Selenastrum capricornutum)	1 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc, Dithiophosphate Di-c1-14-alkyl Esters (CAS Listed.

68649-42-3)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Immediate Hazard - No **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc, Dithiophosphate Di-c1-14-alkyl Esters	68649-42-3	0.1 - 1.0

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Highly Refined Light Mineral Base Oil (CAS 64742-55-8)

Petroleum Base Oil (CAS 64742-52-5)

US. New Jersey Worker and Community Right-to-Know Act

Zinc, Dithiophosphate Di-c1-14-alkyl Esters (CAS 68649-42-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Highly Refined Light Mineral Base Oil (CAS 64742-55-8)

US. Rhode Island RTK

Zinc, Dithiophosphate Di-c1-14-alkyl Esters (CAS 68649-42-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

16. Other information, including date of preparation or last revision

Issue date 01-16-2017

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Version

02

Disclaimer

The information in this document was written based on the best knowledge and experience currently available, and is offered for your consideration and guidance when exposed to this product. KLONDIKE Lubricants Corporation disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this document does not apply to use with any other product or in any other process. This document may not be changed, or altered in any way without the expressed knowledge and permission of KLONDIKE Lubricants Corporation. The information in the sheet was written based on the best knowledge and experience currently available.